

EQUIPMENT

Equipment



KANSO



KS-4001 INFANT INCUBATOR

- Model type: YD-2000
- 1.The main body adopts the integrated plastic materials and the streamline design; has the flexible and push and pull humidity and tilt adjuster, large baby-nursing space;
- 2. Servo-control air temperature or skin temperature by Micro-computer. Humidity and oxygen concentration control (optional); baby electric balance and tray (optional);
- 3. Built-in integrated sensor box, which includes Skin-temp sensor, Air-temp sensor, oxygen concentration sensor, and humidity sensor;
- 4. Double wall hood, Front and back access panel, large mattress, x-ray tray under the bed, heat going out from both side of back and front to increase the inside temperature uniformity;
- 5. LCD digital display, menu operation, >37°C temperature setting, 48 hours screen of remembering curve; 6.Eight self check alarms, RS-232 connector; Central internet monitoring system to infant, Electronic variable resisting, knockdown storage cabinet.
- Other types: YP-90 series, YP-100 series, YP-970, TI-2000



YD-2000

KS-4002 ELECTROCARDIOGRAPH

- Model type: ECG-1212
- Memory of 16 exams
- 6/12 Channel Printout
- Rhythm Lead
- Large LCD for Waveform Preview
- Waveform Measurement and Interpretation
- Simultaneously 12 lead Acquisition
- Standard I/O and RS232 Interface
- Other types:
Single Channel ECG Machine: ECG-11A/B
Single Channel digital RCG Machine: ECG-11D, ECG-11D(II)
Three Channel Interpretive ECG Machine: ECG-32A, ECG-32B, ECG-32(II)
Six Channel Interpretive ECG Machine: ECG-1206
Twelve Channel Interpretive ECG Machine: ECG-1212, ECG-1220



ECG-1212

KS-4003 PULSE OXIMETER

- Model type: TR-900
- SPO2 measuring range: 50%-100%
- Precision: ±2%(90-99%)
±4%(70-89%)
±6%(50-69%)
- Pulse rate range: 30-250bpm
- Accuracy: ±1bpm
- Battery type: 1.2Vx5pcs rechargeable NIMH batteries 2000-2300mAh
- Battery life: Approximately 20 hours
- Alarm Low power light alarm



TR-900

■ KS-4004 MULTI-PARAMETER PATIENT MONITOR

- Model type: TR-900E
- 1、 Portable and colour display.
- 2、 10.4/6.4 inch TFT LCD display with high resolution. Wave-form and Measuring result displayed at the same time.
- 3、 Menu mouse and hotkey make operation more convenient.
- 4、 All lead ECG, more than 20 VPC waveforms are analyzed and Recorded automatically.
- 5、 Manual, Auto and continuation, three kind of NIBP measuring Modes.
- 6、 Freezing and releasing waveform function, analysis of ST-segment, ECG waveform recall, 96 hours trend chart and alarm function. 100 Sets of VPC data and 400 sets of NIBP data are stored.
- 7、 Can be used with ESU, defibrillator and pacemaker simultaneously.
- 8、 Network capacity and can be connected to central monitoring System.
- 9、 Built-in recorder and storage battery are optional.
- Other types:
TR-900D (Desktop) patient monitor
TR-2002 Mother/Fetus Monitor



TR-900E



TR-2002

■ KS-4005 PORTABLE TYPE B ULTRASOUND DIAGNOSTIC SCANNER

- Model type: YD-600
- 1、 Image multiplied : X1、 X1.2、 X1.5、 X2.
- 2、 Image displaying: freeze and defreeze, left and right、 black and white change scrolling and far-field approaching, etc.
- 3、 Measurement and analyze: electronic rule can show distance, area, volume, circumference, heart-rate, etc. BPD、 CRL、 GS、 etc, seven kinds obstetric table available. Connecting the mouse convenient and quick.
- 4、 Mark displaying : time、 ID、 13kind body marks、 focusing position、 frequency letter-note, etc.
- 5、 Piecing: piercing guiding function.
- 6、 Real-time clock displaying: show the date and time automatically.
- 7、 Supplu at optiom VCR、 frozen switch、 trackball、 Piercing accessories、 9 inch monitor.
- Other types: YD-800, YD-800a, YD-800B, YD-600c, YD-500A, YD-500B, YD-500C



YD-600

▪ KS-4006 ULTRASONIC NEBULIZER

- Model types: KCW-5T
- Max capacity of medicine cup: 50ml;
- Capacity of water trough: 250ml
- Nebulizing amount: 3ml/min-5ml/min;
- Gross weight of single package: 3200g, 6 in one package
- Other types: KCW-5TD, KCW-5TSD, KCW-6T, KCW-6TD, KCW-6TYD



KCW-5T



KQW-4A

▪ KS-4007 AIR-COMPRESSING NEBULIZER

- Model type: KQW-4A
- Max capacity of medicine cup: 20ml
- Nebulizer rate: 0.3ml/min
- Particle size rate: $3.2 \mu\text{m}$ (MMD*)
- Residual of a medicine: $\leq 0.5 \text{ ml}$
- Noise: 56dB(A)
- Power consumption: 200VA
- Other types: KQW-4B, KQW-5A

▪ KS-4008 PORTABLE PHLEGM SUCTION UNIT

- Model type: T1-A
- 1. High negative pressure, large flux, low noise.
- 2. adopts advanced overflow-protection design,
- 3. Compact, lightweight, and easy to carry especially suitable for emergency and outside use.
- 4. Voltage: AC220V $\pm 10\%$, 50Hz $\pm 2\%$
- 5. Power: 90VA
- 6. Max negative pressure value: $\geq 0.075 \text{ MPa}$
- 7. Pumping rate: 18L/min
- 8. Reservoir volume: 1000mL



T1-A



▪ KS-4009 RESUSCITATOR

- HF-III: used for adult, the mask coincide with mouth and nose, pressure output adjustable, oxygen pipe, breath soft tube.
- HF-II: for 2-7 years old. Silicon rubber material, circle soft are side mask auto reduce pressure valve, collect gas bag.
- HF-I: neonate infant. Silicon rubber material, circle soft are side mask auto reduce pressure valve, collect gas bag.